

THE UBRIX ADVERTISING EV CHARGER

DC EV CHARGER WITH 55-INCH LED SCREEN



OCPP 1.6J



4G
CONNECTIVITY



WI-FI
CONNECTIVITY



INGRESS
PROTECTION
RATING



IMPACT
PROTECTION
RATING



SWIPE CARD/ POS
(OPTIONAL)



3-YEAR
WARRANTY



www.evenenergy.me
clients@evenenergy.me

Office 215, Tarish Al Hameli Bldg.,
Defese Road, Abu Dhabi
United Arab Emiraes

MODEL UBRIX-55

DC EV CHARGER WITH 55-INCH LED
SCREEN

CHARGE YOUR ELECTRIC VEHICLE
FASTER AND SMARTER WITH OUR DC EV
CHARGER, FEATURING A 55-INCH LED
SCREEN. THIS INNOVATIVE CHARGER
NOT ONLY POWERS YOUR CAR
EFFICIENTLY BUT ALSO PROVIDES A
PLATFORM FOR ADS, NEWS, AND REAL-
TIME UPDATES.

PERFECT FOR SHOPPING CENTERS,
OFFICES, AND PUBLIC SPACES, THE
LARGE SCREEN GRABS ATTENTION AND
KEEPS USERS INFORMED WHILE THEY
CHARGE. ENHANCE YOUR CHARGING
STATION WITH MODERN TECHNOLOGY
AND ENGAGE CUSTOMERS LIKE NEVER
BEFORE.



PARAMETERS

UBRIX-55/ 60KW

ITEM		60kW
	Voltage range	AC380V±20%
	Working frequency	45-65HZ
	The power factor	≥0.99
INPUT	Input current	0-100A
	Input cable length	Non
	Power	60kW
	Auxiliary power supply	GB/T:12V/24V ;CCS1; CCS2; CHAdMO:12V
	Voltage range	200-1000Vdc
	Output current	0-200A
	Charger mode	Single plug Full power charge/Dual plugs AB equalization
OUTPUT	Charger plug	Single plug/Dual plugs
	Cable	Standard 5 meters (head + outlet length 4.5 meters, wire length can be customized)
	Temperature range	-20~50°C; 25°C
	Humidity range	5~90RH%; (non-condensation)
The work environment	Operation altitude	<2000M
	Operation environment	Indoor/outdoor
	Machine size(mm)	920x670x2047mm (Excluding head, handle and casters)
Dimensions and protection	Packing size(mm)	940x1350x2200mm
	Packed weight	About 350KG
	Environment protection	IP54
Starting mode		Plug and play/Swipe start/Input password start/VIN code/POS
Protection function		Scram ; Input over/under voltage ; Output overvoltage ; Overtemperature ;
		Overcurrent ; Short circuit ; Leakage ; Lightning ; Battery reverse; Insulation monitoring ;
Human-computer interaction		55/43-inch advertising screen+7 inch color touch screen
Screen language		Default English, other languages can be customized
Charging mode		Plug and play、OCPP 1.6
Networking mode		4G/WIFI/Ethernet
Installation mode		Floor-mounted



PARAMETERS

UBRIX-55/ 80KW

ITEM		80kW
	Voltage range	AC380V±20%
	Working frequency	45-65HZ
	The power factor	≥0.99
INPUT	Input current	0-134A
	Input cable length	Non
	Power	80kW
	Auxiliary power supply	GB/T:12V/24V ;CCS1; CCS2; CHAdeMO:12V
	Voltage range	200-1000Vdc
	Output current	GB/T:0-250A ;CCS1; CCS2; CHAdeMO:0-200A
	Charger mode	Single plug Full power charge/Dual plugs AB equalization
OUTPUT	Charger plug	Single plug/Dual plugs
	Cable	Standard 5 meters (head + outlet length 4.5 meters, wire length can be customized)
	Temperature range	-20~50°C; 25°C
	Humidity range	5~90RH%; (non-condensation)
The work environment	Operation altitude	<2000M
	Operation environment	Indoor/outdoor
	Machine size(mm)	920x670x2047mm (Excluding head, handle and casters)
Dimensions and protection	Packing size(mm)	940x1350x2200mm
	Packed weight	About 350KG
	Environment protection	IP54
Starting mode		Plug and play/Swipe start/Input password start/VIN code/POS
Protection function		Scram ; Input over/under voltage ; Output overvoltage ; Overtemperature ;
		Overcurrent ; Short circuit ; Leakage ; Lightning ; Battery reverse; Insulation monitoring ;
Human-computer interaction		55/43-inch advertising screen+7 inch color touch screen
Screen language		Default English, other languages can be customized
Charging mode		Plug and play、OCPP 1.6
Networking mode		4G/WIFI/Ethernet
Installation mode		Floor-mounted



PARAMETERS

UBRIX-55/ 120KW

ITEM		120kW
	Voltage range	AC380V±20%
	Working frequency	45-65HZ
	The power factor	≥0.99
INPUT	Input current	0-200A
	Input cable length	Non
	Power	120kW
	Auxiliary power supply	GB/T:12V/24V CCS1; CCS2; CHAdeMO:12V
	Voltage range	200-1000Vdc
	Output current	GB/T:0-250A ;CCS; CHAdeMO:0-200A
	Charger mode	Single plug Full power charge/Dual plugs AB equalization
OUTPUT	Charger plug	Single plug/Dual plugs
	Cable	Standard 5 meters (head + outlet length 4.5 meters, wire length can be customized)
	Temperature range	-20~50°C; 25°C
The work environment	Humidity range	5~90RH%; (non-condensation)
	The altitude	2000M
	Temperature range	Indoor/outdoor
	Machine size(mm)	920x670x2047mm (Excluding head, handle and casters)
Dimensions and protection	Packing size(mm)	940x1350x2200mm
	Packing/weight	About 410KG
	IP	IP54
Starting mode		Plug and play/Swipe start/Input password start/VIN code/POS
Protection function		Scram ; Input over/under voltage ; Output overvoltage ; Overtemperature ; Overcurrent ; Short circuit ; Leakage ; Lightning ; Battery reverse; Insulation monitoring ;
Human-computer interaction		55/43-inch advertising screen+7 inch color touch screen
Screen language		Default English, other languages can be customized
Charging mode		Plug and play、OCPP 1.6
Networking mode		4G/WIFI/Ethernet
Installation mode		Floor-mounted



SCREEN AND MOTHERBOARD PARAMETERS

UBRIX-55

Screen parameter	
Size	55 inches
Aspect ratio	16: 9
Resolution	1920X1080/3840x2160
Display area	1209.6*680.4mm
Brightness	2500 cd/m ²
Contrast	1300:01:00
Viewing angle	178°X178°
Response time	8ms
Life cycle	50000 hours
Power	350W
Voltage	110V/220V,50/60Hz
Power	325W
Motherboard	
Model	RK3568/RK3399/RK3588(Windows 10 optional)
RAM+ROM	2+8 to 8+256
Multi-media	1080P、4K、 H264、 H265 video decoders
OS	Android 7.1/10/11/12
Connectivity	Support RJ45, Ethernet
	Support WIFI, 2.4G/5GWi-Fi (2.4G by default,5G/BT optional)
Video	Support wmv、 avi、 flv、 rmvb、 mp4、 mpeg、 ts, etc.
Image	Support BMP、 JPEG、 PNG、 GIF etc.
USB	6-way USB interface (4-way pin, 2-way standard USB port)
Camera	1x MIPI, max resolution 13 million pixel
HDMI Output	1x HDMI, support 4K/1080P
Audio	Dual channel output, support 2x 8R*3W/4R*6W



ACTUAL IMAGES UBRIX-55

