

THE UBRIX AC ADVERTISING EV CHARGER

AC EV CHARGER WITH 55-INCH LED SCREEN



OCPP 1.6J



**4G
CONNECTIVITY**



**WI-FI
CONNECTIVITY**



**INGRESS
PROTECTION
RATING**



**SWIPE CARD/ POS
(OPTIONAL)**



**2-YEAR
WARRANTY**



Available in :

14kW dual gun

22kW dual gun

44kW dual gun



www.evenenergy.me

clients@evenenergy.me

Office 215, Tarish Al Hameli Bldg.,
Defese Road, Abu Dhabi
United Arab Emiraes

MODEL UBRIX AC-55

AC EV CHARGER WITH 55-INCH LED
SCREEN

INTRODUCING THE AC CHARGER WITH
A 55" ADVERTISING SCREEN - A
PERFECT FUSION OF CONVENIENCE
AND INNOVATION. THIS UNIQUE
SOLUTION COMBINES A RELIABLE
CHARGING STATION WITH A VIBRANT
DIGITAL DISPLAY, OFFERING
BUSINESSES AN IMPACTFUL WAY TO
ENGAGE AND INFORM CUSTOMERS.
IDEAL FOR RETAIL SPACES, MALLS, OR
PUBLIC AREAS,

UBRIX AC CHARGER WITH A 55"
SCREEN ENHANCES THE CUSTOMER
EXPERIENCE WHILE PROVIDING A PRIME
PLATFORM FOR ADVERTISING. POWER
UP AND SHOWCASE YOUR BRAND WITH
ONE DYNAMIC SOLUTION.



PARAMETERS

UBRIX AC-55

Technical Features			
Charging capacity	Up to 14KW (7KW*2)	Up to 22KW (11KW*2)	Up to 44KW (22KW*2)
Input/Output power	230VAC±20%-50/60Hz-	400VAC±20%-50/60Hz-	400VAC±20%-50/60Hz-
	32A*2-1phase	16A*2-3phase	32A*2-3phase
RCD	RCMU(Type A+ DC 6mA)/ Type B RCCB(Optional)		
Standby power	<5W		
Measuring accuracy	1%		
Energy Meter	MID certified		
OCPP	OCPP1.6 Json(OCPP2.0 optional)		
Communication	WIFI/Ethernet/4G(Optional)		
User interface	LCD 5 inch Touch Screen/ RFID(mifare iso& IEC 14443A)		
Certificate/Compliance	CE/FCC/ROHS/REACH/IEC/EN 61851-1, IEC/EN61851-21-2, IEC/EN 62955, EN300328, EN 301489-1/-17,EN62479.		
Charging Interface	Type 2 socket*2 or Type 2 Gun *2 5M		
Special Protection	Over current protection, Residual current protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection		
Advertising Display			
LCD screen	55”IPS 1920*1080 16:9 HDV 2500cd/m²		
Application platform	Android 4.3 and above		
Communication	WIFI/Ethernet/4G(Optional)		
Ad update	USB flash disk,SD card, wired network remote release		
Physical Properties			
Warranty	2 years		
Protection	IP55(outdoor)		
Special Protection	Topple & fall down protection		
Cooling	Natural cooling		
Operating temperature	-20C° to +55C°		
Humidity	Max.95%(non-regulating)		
Product Dimension	1950*920*290mm		
Package Dimension	2110*450*1170mm(L*W*H)		
Net Weight	145kg		
GrossWeight.	201Kg		



ACTUAL IMAGES UBRIX AC-55

