

# ZENO 22KW-WS

## 22KW AC WALLBOX CHARGER WITH FRONT SOCKET

BY: EV ENERGY SOLUTIONS LLC SPC

ABU DHABI, UNITED ARAB EMIRATES

[WWW.EVENERGY.ME](http://WWW.EVENERGY.ME)



# ZENO 22KW-WS

22KW AC WALLBOX CHARGER WITH FRONT SOCKET

---

## SPECIAL FEATURES

- 3.5 INCHES LED TOUCH SCREEN
- APP (TUYA)
- CT AND LOAD BALANCING (OPTIONAL)
- OCPP & 4G (OPTIONAL)
- IP65 RATED
- IK08 RATED
- TUV CERTIFIED
- MATERIAL: PC+ASA
- HOUSING MATERIAL OFFERS MECHANICAL STRENGTH, WEATHER & UV RESISTANCE



| Item              | Specification                |                                                                  |                |                |
|-------------------|------------------------------|------------------------------------------------------------------|----------------|----------------|
| Name              | POWER                        | AC 7kW                                                           | AC 11kW        | AC 22kW        |
|                   | Temperature                  | -30°C ~ 55°C                                                     |                |                |
| Environment       | Humidity                     | 5% to 95% no congeal                                             |                |                |
|                   | Altitude height              | 2000m                                                            |                |                |
|                   | Size                         | 23*33*10 cm                                                      |                |                |
| Electrical        | RCD                          | Type A+DC 6mA                                                    |                |                |
|                   | Input voltage                | 1/N/PE ~ 230V                                                    | 3/N/PE ~ 380V  | 3/N/PE ~ 380V  |
|                   | Input frequency              | 50Hz                                                             |                |                |
|                   | The max power                | 7kW                                                              | 11kW           | 22kW           |
|                   | Electric relay specification | 50A 250VA                                                        |                |                |
|                   | Rated Output                 | max output 32A                                                   | max output 16A | max output 32A |
|                   | Cable Length                 | 5 meter output cable, no input cable in default                  |                |                |
| Structure         | Charging Method              | RFID(Optional) card / plug and charge /APP/ Reservation charging |                |                |
|                   | Application                  | Indoor/Outdoor                                                   |                |                |
| Optional Function | Load Balance                 | CT+Single/Three Phase Meter                                      |                |                |
|                   | OCPP                         | 4G/Ethernet                                                      |                |                |
|                   | Screen                       | Screen is removable if not needed                                |                |                |